



KING METAL (HK) CO., LTD.

ADDRESS: 3F Quanqutong Bldg., Zhangjiagang Free Trade Zone

Zhangjiagang, Jiangsu, China


Tel: 86-512-58323359 | Fax: 86-512-58323389 | Mobile: 86-18915691035





E-mail: kingmetal@kingmetal.hk

MSN: chenhanzhu@hotmail.com | Skype: kingmetalk

Website: www.kingmetal.hk; www.alucowall.com; www.mulrich.net.cn

CATALOGUE

GOODS	PHOTO	SPEC.	Trade Terms
Galvanized		<p>Name: Hot Dipped Galvanized Steel</p> <ol style="list-style-type: none"> Standard: DX51D, SGCC, S350GD, S280GD... Thickness: maximum 5.00mm Width: ≤1500mm Zinc Coating: Z60-Z350g/m² Surface Treatment: chromium-free passivation, phosphated, skin-passed, anti-finger, oiled Spangle: zero, minimum, regular or big spangle Sheet and Strip are both available Application: suitable for countless outdoor, marine or industrial applications 	FOB,CIF, CNF/CFR
Aluzinc / Galvalume		<p>Name: Aluzinc / Galvalume Steel</p> <ol style="list-style-type: none"> Standard: DX51D, SGCC, G550, G300... Thickness: maximum 2.00mm Width: ≤1250mm AZ coating: AZ50-AZ275g/m² Component: 55% Al, 43.5% Zn and 1.5% Si Surface Treatment: anti-finger, skin-passed, chromated, oiled Sheet and Strip are both available Application: suitable for countless outdoor, marine or industrial applications 	FOB,CIF, CNF/CFR
Prepainted		<p>Name: Prepainted Steel</p> <ol style="list-style-type: none"> Base material: GI, Aluzinc, and CR Thickness: maximum 1.00mm Width: ≤1250mm Coating: Z60-Z200g/m² or AZ50-AZ150g/m² Color: any color by your samples or as per RAL Color Chart Protective film is available, easy to move away Application: suitable for roof tiles, ceiling, whiteboard, doors and windows, electronic household appliances, etc. 	FOB,CIF, CNF/CFR
Multicolor Steel for Multi Purposes		<p>Name: Multicolor Steel</p> <ol style="list-style-type: none"> Base Material: GI, Aluzinc, and CR Thickness: maximum 1.00mm Width: ≤1250mm Coating: Z60-Z200g/m² or AZ50-AZ150g/m² Paint: PE, PVDF and SMP Color: any color, any design. such as wood, marble, brick, camouflage patterns Good adhesive and can be roll forming Protective film is available Application: suitable for roof tiles, ceiling, doors and windows, electronic household appliances, etc. 	FOB,CIF, CNF/CFR

<p>PVC / PET Laminate Steel Sheet</p>		<p>Name: PVC / PET Laminate Steel Sheet 1. Base Material: GI, Aluzinc, and CR 2. Thickness: maximum 1.00mm 3. Width: ≤1250mm 4. Laminate Film: PVC, PET 5. Pattern: plain; wood; embossed; shine 6. Protective film is available, easy to move away 7. T bend: 0T can be achieved 8. Application: electronic household appliances, doors and windows, industrial application</p>	<p>FOB,CIF, CNF/CFR</p>
<p>PCM for Household Electric Appliances</p>		<p>Name: PCM Steel 1. Base Material: GI, Aluzinc, and CR 2. Thickness: maximum 1.00mm 3. Width: ≤1250mm 4. T bend: 0-3T 5. Pencil hardness: 40-60HB 6. Gloss: 20%-90% 7. Color: any color by buyers' color samples 8. Protective film is available, easy to move away 9. Application: electronic household appliances</p>	<p>FOB,CIF, CNF/CFR</p>
<p>CRNGO Silicon Steel</p>		<p>Name: Cold Rolled Non Grain Oriented Silicon Steel 1. Thickness: 0.50mm 2. Width: 1000-1200mm 3. Type: W600/W800/W1300 4. Material: NON-GRAIN Oriented 5. Package: Export Standard Package 6. Usage: Transformer, Stator, Motor Lamination, etc.</p>	<p>FOB,CIF, CNF/CFR</p>
<p>Cold Rolled</p>		<p>Name: Cold Rolled Steel 1. Thickness: maximum 2.00mm 2. Width: ≤1250mm 3. Grade: Q195, Q195L, SPCC, SAE1006-1008 4. Surface treatment: oiled, bright or matte Finish 5. Packing: Standard export package 6. Application: refrigerators, drums and pails, tubing, strapping, and coil coating</p>	<p>FOB,CIF, CNF/CFR</p>



Payment Term

L/C, TT

L/C, TT

L/C, TT

L/C, TT

L/C, TT

L/C, TT

L/C, TT

L/C, TT