






## \* PRODUCT DATASHEET

- \* Model:HX-15-15 (polishing surface)  
HX-15-15M (matte surface)  
HX-15-15L (beads surface)
- \* Dimensions:  
Lens:  $\Phi 15.00\text{mm}$  H9.12mm  
Cone holder:  $\Phi 17.00\text{mm}$  H10.00mm  
bipod striped cylinder holder: N/A
- \* Materials:  
Lens: Optical Grade PMMA PC  
Holder: ABS
- \* Assembly Dimensions:  
Lens with cone holder:  $\Phi 17.00\text{mm}$  H10.00mm  
Lens with bipod striped cylinder holder: N/A
- \* Surface Treatment: Polishing | Matte | Beads surface
- \* Beam Angle: 15deg
- \* For Led:  
CREE XP-C/E/G  Seoul Z5P   
CREE XT-E  Oslon CP7P   
CREE XB-D 
- \* Certification: SGS RoHs



- \*Features:  
High efficiency  
Available in 1 beam Patterns  
Optimized for uniform effects  
Lens with holder
- \*Typical applications:  
Stage lighting  
Street lights  
Decorative light  
Architectural lighting  
Down light  
Flishlight

## \* Brief description :

\*The OPTIC-FOV (Shenzhen Hongxuan Optoelectronic Technology Co., Ltd) lens offers low-profile lenses specifically designed for the Luxeon® LEDs, Edison® LEDs ,Bridgelux® LEDs CREE® LEDs or Seoul® LEDs.

\*A software-optimized aspheric profile enables the generation of several different beam output patterns:narrow,medium,elliptical and wides beams.

The high collection efficiency reaches 85% of the total flux emitted by the LEDs.

\*Lens holders are available in white or black,and provide the proper alignment the between the LEDs and the lenses,set correct distance between the lens and LED.

\*The lens holder can be glued to the PCB to provide a secure assembly.




Company: Shenzhen Hongxuan Optoelectronic Technology Co., Ltd  
Address: the 5-7 building, Tongsheng development zone, Dalang Longhua town, Baoan district , Shenzhen city, Guangdong China

Tel: 0086-755-61186096 Fax: 0086-755-61162768 Email: opticfov@gmail.com

Website: www.optic-fov.com




**\* Holder and Lens dimensions of the 2D views**



**\* Beam Pattern**



**\* Angular Intensity Distribution**



**\* Typical illuminance value**

Normal Distance (m)	1.5	2	5	9
Illuminance (lux <sub>1W led</sub> )	742	418	67	21
Illuminance (lux <sub>3W led</sub> )	N/A	N/A	N/A	N/A

Notes:

\*Cree flux characteristics at IF=350mA and TJ=25°C: for 1W Q5 (Part Name: XPGWHT-L1-0000-00DE4/Neutral White/107lm/Lambertian LED)

\*Performance values given are typical values and will vary dependant on LED binning, colour and drive profile

\*Typical illuminance value is reference date (Receiving surface of the average illuminance values).



## \* LED Lens materials feature table

Items	Features	Experimental methods	Units	PMMA
Physical properties	Density	ASTM D792	g/cm	1.19
	Absorbption	ASTM D570	%	2
Optical properties	Refraction index	ASTM D542		1.49
	Transmittance	ASTM D1003	%	95
	ABBE	ASTM D542		58
	Birefringence		nm	<20
Thermodynamical properties	Glass transition point	DSC	°C	150
	Heat distortion	ASTM D648 (1.85kg/cm)	°C	120
Mechanical properties	Tensile strength	ASTM D638	MPA	730
	Tensile elongation	ASTM D638	%	10
	Flexural modulus	ASTM D790	10MPA	3

## \* Notes:

- 1.Engineering drawings and all dimensions are in millimeters,holder and lens tolerance,respectively  $\pm 0.10$  and  $\pm 0.05$ .
- 2.Product operating temperature range  $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$  (upper limit  $+80^{\circ}\text{C}$ ).
- 3.Product storage temperature range  $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$  (upper limit  $+80^{\circ}\text{C}$ ).
- 4.Average transmittance in visible specturm  $400\text{nm} \sim 700\text{nm} > 92\%$ .
- 5.If necessary,clean lenses with mild soap water and soft cloth.
- 6.Never use any commercial cleaning solvents on lenses,like alcohol.
- 7.Please handle and install lenses with wearing gloves,skin oils may damage lens or its optical characteristic.

